


MM-S




METRIC MALE - 24° CONE SEAT - HEAVY DUTY MASCHIO METRICO - SVASATO 24° - SERIE PESANTE

CES

TIEFFE Part.N.	Hose Size			METRIC 24° Connection		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	F	Pipe	H	L	S			bar	PSI
CH12MM20S	19	3/4"	-12	M 30x2	20S	31	93	30			420	6000
CH12MM25S	19	3/4"	-12	M 36x2	25S	35	97	36			420	6000
CH16MM25S	25	1"	-16	M 36x2	25S	36	109	36			380	5500
CH16MM30S	25	1"	-16	M 42x2	30S	40	113	46			380	5500
CH20MM30S	31,5	1 1/4"	-20	M 42x2	30S	42	130	46			325	4700
CH20MM38S	31,5	1 1/4"	-20	M 52x2	38S	46	134	55			325	4700
CH24MM38S	38	1 1/2"	-24	M 52x2	38S	47	141	55			290	4200

FOS-S



METRIC FEMALE 24° O-RING CONE - HEAVY DUTY - SLIP-ON NUT FEMMINA METRICA OGIVA 24° O-RING - SERIE PESANTE - DADO LIBERO

DKOS

TIEFFE Part.N.	Hose Size			METRIC 24° Connection		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	F	Pipe	H	L	S	O-RING		bar	PSI
CH12FOS20S	19	3/4"	-12	M 30x2	20S	33	95	36	16,3x2,4		420	6000
CH12FOS25S	19	3/4"	-12	M 36x2	25S	36	98	46	20,3x2,4		420	6000
CH16FOS25S	25	1"	-16	M 36x2	25S	37	110	46	22x2		380	5500
CH16FOS30S	25	1"	-16	M 42x2	30S	39	112	50	25,3x2,4		380	5500
CH20FOS30S	31,5	1 1/4"	-20	M 42x2	30S	41	128	50	25,3x2,4		325	4700
CH20FOS38S	31,5	1 1/4"	-20	M 52x2	38S	43	131	60	33,3x2,4		325	4700
CH24FOS38S	38	1 1/2"	-24	M 52x2	38S	44	138	60	33,3x2,4		290	4200